

HEAT TREATABLE STEELS AND PRECIPITATION HARDENING STEELS

A	12 42		
ADD	lication	Segment	S

Aerospa	ce
ACIOSPU	CC

Available Product Variants

Long Products*	
----------------	--

Plates

Product Description

BÖHLER V300 covers a premium aircraft-quality, maraging alloy steel in the form of bars, forgings and stock for forging up through 10 inches (254.00 mm) inclusive in diameter or least distance between parallel sides.

In contrast to heat treatable steels its outstanding tensile properties are not due to a hardened structure with relatively high carbon content, but to precipitation of intermetallic phases from a ductile nickel bearing matrix containing almost no carbon.

These products have been used typically for parts requiring through hardening, without quenching, to a minimum yield strength of 270 ksi (1862 MPa) and where such parts may require welding during fabrication, but usage is not limited to such applications. E.g highly stressed components for the aircraft and rocket industries.

Process Melting

VIM + VAR

Applications

> Structural parts (Aerosp)

> Other Aerospace Comps.

Technical data

Material designation		Standards	
Maraging 300	Market grade	6514	AMS
1.6354	SEL		

Chemical composition (wt. %)

С	Si	Mn	P	S	Cr	Мо	Ni	Cu	Со	Ti	Al	В	Ca	Zr
max.	max.	max.	max.	max.	max.	4.60 to	18.00 to	max.	8.50 to	0.50 to	0.05 to	max.	max.	max.
0.03	0.10	0.10	0.010	0.010	0.50	5.20	19.00	0.50	9.50	0.80	0.15	0.004	0.05	0.02

Related to AMS 6514



^{*)} Presented data refer exclusively to long products. Please observe the detailed explanations at the end of the data sheet (pdf).



HEAT TREATABLE STEELS AND PRECIPITATION HARDENING STEELS



Delivery condition

Solution annealed										
Hardness (HRC) max. 36 Above 12.7 mm diameter										
Solution annealed										
Solution annealed Hardness (HRC)	max. 36 Max 12.7 mm diameter									

Round Bars and Wire Rod (if any)

Diameter					MOQ ex mill				Len	Tolerance			
mn	า	inch		า	kg	lbs	m			ft			
ROLLED													
-	12.49	0.197	-	0.492	1,100	2,425	3.00	-	4.00	9.84	-	13.12	IT h/k 11
-	55.00	0.492	-	2.165	1,300	2,866	3.00	-	4.00	9.84	-	13.12	IT h/k 11
-	120.00	2.166	-	4.724	2,500	5,512	3.00	-	4.00	9.84	-	13.12	IT h/k 11
-	140.00	4.725	-	5.512	2,500	5,512	3.00	-	5.00	9.84	-	16.40	IT h/k 14
FORGED													
-	203.20	5.512	-	8.000	2,200	4,850	3.00	-	5.00	9.84	-	16.40	IT h/k 14
		- 12.49 - 55.00 - 120.00 - 140.00	- 12.49 0.197 - 55.00 0.492 - 120.00 2.166 - 140.00 4.725	- 12.49 0.197 55.00 0.492 120.00 2.166 140.00 4.725 -	- 12.49 0.197 - 0.492 - 55.00 0.492 - 2.165 - 120.00 2.166 - 4.724 - 140.00 4.725 - 5.512	inch kg - 12.49	nm inch kg lbs ROLLED - 12.49 0.197 - 0.492 1,100 2,425 - 55.00 0.492 - 2.165 1,300 2,866 - 120.00 2.166 - 4.724 2,500 5,512 - 140.00 4.725 - 5.512 2,500 5,512 FORGED	nm inch kg lbs ROLLED - 12.49 0.197 - 0.492 1,100 2,425 3.00 - 55.00 0.492 - 2.165 1,300 2,866 3.00 - 120.00 2.166 - 4.724 2,500 5,512 3.00 - 140.00 4.725 - 5.512 2,500 5,512 3.00 FORGED	nm inch kg lbs m ROLLED - 12.49 0.197 - 0.492 1,100 2,425 3.00 - - 55.00 0.492 - 2.165 1,300 2,866 3.00 - - 120.00 2.166 - 4.724 2,500 5,512 3.00 - - 140.00 4.725 - 5.512 2,500 5,512 3.00 - FORGED	hm inch kg lbs m ROLLED - 12.49 0.197 - 0.492 1,100 2,425 3.00 - 4.00 - 55.00 0.492 - 2.165 1,300 2,866 3.00 - 4.00 - 120.00 2.166 - 4.724 2,500 5,512 3.00 - 4.00 - 140.00 4.725 - 5.512 2,500 5,512 3.00 - 5.00 FORGED	hm inch kg lbs m ROLLED - 12.49 0.197 - 0.492 1,100 2,425 3.00 - 4.00 9.84 - 55.00 0.492 - 2.165 1,300 2,866 3.00 - 4.00 9.84 - 120.00 2.166 - 4.724 2,500 5,512 3.00 - 4.00 9.84 - 140.00 4.725 - 5.512 2,500 5,512 3.00 - 5.00 9.84 FORGED	nm inch kg lbs m ft ROLLED - 12.49 0.197 - 0.492 1,100 2,425 3.00 - 4.00 9.84 - - 55.00 0.492 - 2.165 1,300 2,866 3.00 - 4.00 9.84 - - 120.00 2.166 - 4.724 2,500 5,512 3.00 - 4.00 9.84 - - 140.00 4.725 - 5.512 2,500 5,512 3.00 - 5.00 9.84 - FORGED	nm inch kg lbs m ft ROLLED - 12.49 0.197 - 0.492 1,100 2,425 3.00 - 4.00 9.84 - 13.12 - 55.00 0.492 - 2.165 1,300 2,866 3.00 - 4.00 9.84 - 13.12 - 120.00 2.166 - 4.724 2,500 5,512 3.00 - 4.00 9.84 - 13.12 - 140.00 4.725 - 5.512 2,500 5,512 3.00 - 5.00 9.84 - 16.40

Long Products: For additional specifications, technical requirements, and other dimensions, please contact our regional voestalpine BÖHLER sales companies.

Sheet & Plates: Product Variant may differ in terms of melting process, technical data, delivery, and surface condition as well as available product dimensions. Please contact voestalpine BÖHLER Bleche GmbH & Co KG.

The data contained in this brochure is merely for general information and therefore shall not be binding on the company. We may be bound only through a contract explicitly stipulating such data as binding. Measurement data are laboratory values and can deviate from practical analyses. The manufacture of our products does not involve the use of substances detrimental to health or to the ozone layer.

voestalpine BÖHLER Edelstahl GmbH & Co KG

Mariazeller Straße 25 8605 Kapfenberg, AT T. +43/50304/20-0 E. info@bohler-edelstahl.at https://www.voestalpine.com/bohler-edelstahl/de/

